

Recessed rotating LED Down light with incorporated electronic gear and Chip on board. Improved color rendering index +90. High quality reflector with four different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long life-time and low weight. Adjustable light direction using gyro function.



**Technical data**

Main input voltage	220-240V
Colour temperature	3000 K
CRI	>90
SDCM	3
Luminaire output/Energy consumption	
- Slim I 3000	2800 lm / 24 W
- Slim I 4000	3850 lm / 35 W
Total weight	1,6kg
Form of protection	IP 20, class III
Maximum number of drivers per fuse	10A type C: 36 pcs (24 W) 16A type C: 58 pcs (24W)

Description	Reflector	Art.no	Last digit	Colour
Slim I 3000	Spot	2140331_	1	White
	Medium	2140332_	2	Grey
	Flood	2140333_	3	Black
	Wide Flood	2140334_		
Slim I 4000	Spot	2140391_		
	Medium	2140392_		
	Flood	2140393_		
	Wide Flood	2140394_		

**Miscellaneous**

Seperate electronic gear with 2,5 m cord and plug.  
Product available in other Kelvin temperatures.  
Protection glass (PG) is optional.  
DALI dimming on request.



A=233 B=161 C=200 (mm)



Saw instruction: 220x187 mm